


1. Present a Mealy Model finite state machine that reads an input $x \in \{0, 1\}^*$ and produces the binary number that represents the result of adding the two's complement representation of decimal **-6**, that is adding binary **1...1010** to x (this assumes all numbers are in two's complement notation, including results). Assume that x is read starting with its least significant digit.
Examples: **00010** \rightarrow **11100**; **11001** \rightarrow **10011**; **01011** \rightarrow **00101**

2.

- a.) Let L be defined as the language accepted by the finite state automaton $\mathbf{A} = (\{A, B, C\}, \{0, 1\}, \delta, A, \{C\})$:



Present a right linear grammar that generates the language L .

- b.) Consider the regular grammar $\mathbf{G} = (\{S, A, B\}, \{0, 1\}, \mathbf{R}, S)$, where \mathbf{R} is:

$$\begin{array}{l}
 S \rightarrow 0S \mid 1A \mid 0 \\
 A \rightarrow 1B \mid \lambda \\
 B \rightarrow 0S
 \end{array}$$

Present an automaton \mathbf{A} that accepts the language generated by the \mathbf{G} :

3. Assuming you have computed the sets, $R_{i,j}^k$, for each pair of states, (q_i, q_j) , in some DFA. How is $R_{i,j}^{k+1}$ calculated, where $k+1$ is no greater than the number of states in the associated DFA?

4. Analyze the following language, L , proving it is **non-regular** by showing that there are an **infinite** number of equivalence classes formed by the relation R_L defined by:

$$x R_L y \text{ if and only if } [\forall z \in \{a,b,c\}^*, xz \in L \text{ exactly when } yz \in L].$$

where

$$L = \{ c^k a^n b^m \mid n < m, k > 0 \}.$$

You don't have to present all equivalence classes, but you must demonstrate a pattern that gives rise to an infinite number of classes, along with evidence that these classes are distinct from one another.

5. Write a context-free grammar for the language $L = \{ c^k a^n b^m \mid n < m, k > 0 \}$. Yes, this is the one you just showed is not Regular.

6. Which of the following are correct definitions of an ambiguous grammar? Write **T**(true) or **F**(false).

There are two distinct derivations of some string w derived by the grammar _____

There are two distinct parse trees for some string w derived by the grammar _____

7. Use the Pumping Lemma for context-free languages to show $L = \{ a^n b^{n^2} \mid n > 0 \}$ is **not** a CFL.
Be complete and remember to differentiate what you get to do and what the PL gets to do.

8. Consider the CFG $G = (\{ S, T \}, \{ a, b \}, R, S)$ where R is:

$S \rightarrow a T T \mid T S \mid a$

$T \rightarrow b S T \mid b$

- a.) Present a pushdown automaton that accepts the language generated by this grammar. You may (and are encouraged) to use a transition diagram where transitions have arcs with labels of form $a, \alpha \rightarrow \beta$ where $a \in \Sigma \cup \{\lambda\}$, $\alpha, \beta \in \Gamma^*$. Note: I am encouraging you to use extended stack operations.

What parsing technique are you using? (Circle one) **top-down** or **bottom-up**

How does your PDA accept? (Circle one) **final state** or **empty stack** or **final state and empty stack**

What is the **initial state**? _____

What is the **initial stack content**? _____

What are your **final states** (if any)? _____

- b.) Now, using the notation of **IDs** (Instantaneous Descriptions, $[q, x, z]$), describe how your PDA accepts strings generated by G .

9. Consider the context-free grammar $G = (\{ S, B, E \}, \{ 0, 1, i, e, s \}, R, S)$, where R is:

$$S \rightarrow i B S E \mid s$$

$$B \rightarrow 0 \mid 1$$

$$E \rightarrow \lambda \mid e S$$

a.) Remove all λ -rules from G , creating an equivalent grammar G' . Show all rules, including copied ones.

b.) Convert grammar G' to its Chomsky Normal Form equivalent, G'' . Show all rules, including copied ones from part (a).

10. Let \mathbf{C} be some class of formal languages that is closed under substitution of members of its own class and under intersection with Regular Languages. Prove that \mathbf{C} is also closed under **RealWrappers**, where $\text{RealWrappers}(L) = \{ xz \mid x, z \in \Sigma^+, \exists y \in \Sigma^+, w = xyz \in L \}$. You may assume substitution $f(a) = \{a, a'\}$, and homomorphisms $g(a) = a'$ and $h(a) = a, h(a') = \lambda$. Here $a \in \Sigma$ and a' is a new character associated with each $a \in \Sigma$.

11. Fill in the following table with **Y** (yes) or **N** (no) in each cell, depending upon whether or not the class of languages is closed under the stated operation.

	Regular Languages	Context Free Languages
Concatenation with Regular		
Quotient with Regular		
Complementation		
Superset		

12. Present the **CKY** recognition matrix for the string $v + (v - v)$ assuming the Chomsky Normal Form grammar specified by the grammar

$G = (\{ E, A, B, T, U, L, R, P, M \}, \{ v, +, -, (,) \}, \text{Rules}, E)$, where the **Rules** set is:

- $E \rightarrow EA \mid EB \mid LU \mid v$
- $A \rightarrow PT$
- $B \rightarrow MT$
- $T \rightarrow LU \mid v$
- $U \rightarrow ER$
- $L \rightarrow ($
- $R \rightarrow)$
- $P \rightarrow +$
- $M \rightarrow -$

	v	+	(v	-	v)
1							
2							
3							
4							
5							
6							
7							

*Note: Do not be surprised if the above table is sparsely populated.
Hint: Be concerned if it's densely populated.*