

**University of Central Florida  
School of Computer Science  
COT 4210      Spring 2004**

**Prof. Rene Peralta  
Homework 7**

**Due date: April 19**

1. The following is a hierarchy of subsets of  $\mathbb{N}$ .

$$\text{regular} \subseteq \text{CFL} \subseteq \text{recursive} \subseteq \text{re.} \subseteq P(\mathbb{N})$$

Show that the hierarchy is proper by giving examples of sets contained in each level but not in the next one.

2. In this question, let  $M$  be a Turing machine which takes as input a positive integer  $i$  and outputs (if it halts) a positive integer  $M(i)$ . Denote by  $L_M$  the language  $\{M(i) \mid i = 1, 2, 3, \dots\}$ .

Answer True or False (no need to justify your answer, do so at your own peril). Score is +1 for correct answer, -1 for incorrect answer.

- (a) It is always true that the language  $L_M$  is recursive.
- (b) The set of languages over  $\{0, 1\}$  recognized by C programs is countable.
- (c) There exists a language recognized by  $M$  but not recognized by any Finite Automaton.
- (d) Let  $H$  be the language composed of Turing machine representations which halt iff the input is an even number. Then  $H$  is computable in polynomial time.
- (e) A simple argument for the existence of non-regular languages is that the set of DFAs is countable but the set of languages is not. However, Turing machines are allowed to have an infinite tape and therefore this argument cannot be used to prove the existence of non-recursively enumerable languages.
- (f) The reversal of a deterministic CFL is always a deterministic CFL.

- (g) There exists a language recognized by a PDA but not recognized by any C program.
- (h) The complement of a recursively enumerable language is recursively enumerable.
- (i) The set of all languages over  $\Sigma = \{0, 1\}$  is countable.
- (j) The complement of a CFL is always a CFL.
- (k) Any language over the binary alphabet is recognized by some Turing machine.
- (l) The complement of a recursive language is always recursive.
- (m) Define a “bounded-stack” PDA (abbreviated BS-PDA) as a PDA that halts whenever the depth of the stack is greater than some fixed bound  $T$  (note different BS-PDAs can have different bounds on the stack depth). Then every CFL can be recognized by a BS-PDA.

3. A “path” in a graph is a sequence of distinct adjacent vertices. Consider the language

$$L = \{(G, B) \mid B \in \mathbb{N}, G \text{ a graph containing a path of length } B\}.$$

There is no known practical algorithm that decides membership in  $L$ . But suppose you find an oracle that decides membership in  $L$ . Given a graph  $G$  with  $n$  vertices:

- (a) How many questions to the oracle are sufficient to find the length of a longest path in  $G$ ? Explain.
- (b) How many questions are sufficient to actually find a longest path? Explain